



AD NO. \_\_\_\_\_  
 DTC PROJECT NO. 8-CO-160-UXO-021  
 REPORT NO. ATC-9181



STANDARDIZED  
 UXO TECHNOLOGY DEMONSTRATION SITE  
 BLIND GRID SCORING RECORD NO. 764

SITE LOCATION:  
 U.S. ARMY ABERDEEN PROVING GROUND

DEMONSTRATOR:  
 VF WARNER AND ASSOCIATES, INC.  
 6832 OLD DOMINION DRIVE  
 MCLEAN, VA 22101

TECHNOLOGY TYPE/PLATFORM:  
 MULTI CHANNEL DETECTOR SYSTEM  
 (AMOS)/TOWED

PREPARED BY:  
 U.S. ARMY ABERDEEN TEST CENTER  
 ABERDEEN PROVING GROUND, MD 21005-5059

APRIL 2006



Prepared for:  
 U.S. ARMY ENVIRONMENTAL CENTER  
 ABERDEEN PROVING GROUND, MD 21010-5401

U.S. ARMY DEVELOPMENTAL TEST COMMAND  
 ABERDEEN PROVING GROUND, MD 21005-5055

DISTRIBUTION UNLIMITED, APRIL 2006.

## DISPOSITION INSTRUCTIONS

The use of trade names in this document does not constitute an official endorsement or approval of the use of such commercial hardware or software. This document may not be cited for purposes of advertisement.

| REPORT DOCUMENTATION PAGE  |                             |                              | Form Approved<br>OMB No. 0704-0188                          |  |
|--|-----------------------------|------------------------------|---|--|
| <p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p><b>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</b></p> |                             |                              |   |  |
| 1. REPORT DATE (DD-MM-YYYY)<br>April 2006  |                             | 2. REPORT TYPE<br>Final      |   | 3. DATES COVERED (From - To)<br>23 through 25 January 2006 |
| 4. TITLE AND SUBTITLE<br>STANDARDIZED UXO TECHNOLOGY DEMONSTRATION SITE<br>BLIND GRID SCORING RECORD NO. 764 (VF WARNER AND<br>ASSOCIATES, INC.)   |                             |                              | 5a. CONTRACT NUMBER   |  |
|  |                             |                              | 5b. GRANT NUMBER  |  |
| 6. AUTHOR(S)<br>Overbay, Larry; Watts, Kimberly<br>The Standardized UXO Technology Demonstration Site Scoring Committee  |                             |                              | 5c. PROGRAM ELEMENT NUMBER                                  |  |
|  |                             |                              | 5d. PROJECT NUMBER<br>8-CO-160-UXO-021                      |  |
|  |                             |                              | 5e. TASK NUMBER   |  |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)<br>Commander<br>U.S. Army Aberdeen Test Center<br>ATTN: CSTE-DTC-AT-SL-E<br>Aberdeen Proving Ground, MD 21005-5059  |                             |                              | 5f. WORK UNIT NUMBER  |  |
|  |                             |                              | 8. PERFORMING ORGANIZATION<br>REPORT NUMBER<br>ATC-9181     |  |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)<br>Commander<br>U.S. Army Environmental Center<br>ATTN: SFIM-AEC-ATT<br>Aberdeen Proving Ground, MD 21005-5401   |                             |                              | 10. SPONSOR/MONITOR'S ACRONYM(S)                            |  |
|  |                             |                              | 11. SPONSOR/MONITOR'S REPORT<br>NUMBER(S)<br>Same as Item 8 |  |
| 12. DISTRIBUTION/AVAILABILITY STATEMENT<br>Distribution unlimited.   |                             |                              |   |  |
| 13. SUPPLEMENTARY NOTES  |                             |                              |   |  |
| 14. ABSTRACT<br>This scoring record documents the efforts of VF Warner and Associates, Inc. to detect and discriminate inert unexploded ordnance (UXO) utilizing the APG Standardized UXO Technology Demonstration Site Blind Grid. Scoring Records have been coordinated by Larry Overbay and the Standardized UXO Technology Demonstration Site Scoring Committee. Organizations on the committee include, the U.S. Army Corps of Engineers, the Environmental Security Technology Certification Program, the Strategic Environmental Research and Development Program, the Institute for Defense Analysis, the U.S. Army Environmental Center, and the U.S. Army Aberdeen Test Center.  |                             |                              |   |  |
| 15. SUBJECT TERMS<br>VF Warner and Associates, Inc., UXO Standardized Technology Demonstration Site Program, Blind Grid, Multi Channel Detector System (AMOS)/Towed, MEC   |                             |                              |   |  |
| 16. SECURITY CLASSIFICATION OF:  |                             |                              | 17. LIMITATION OF<br>ABSTRACT<br><br>UL                     | 18. NUMBER<br>OF<br>PAGES                                  |
| a. REPORT<br>Unclassified  | b. ABSTRACT<br>Unclassified | c. THIS PAGE<br>Unclassified |   |  |
|  |                             |                              | 19a. NAME OF RESPONSIBLE PERSON                             |  |
|  |                             |                              | 19b. TELEPHONE NUMBER (Include area code)                   |  |

## **ACKNOWLEDGMENTS**

### **Authors:**

Rick Fling  
Aberdeen Test and Support Services (ATSS)  
Sverdrup Technology, Inc.  
U.S. Army Aberdeen Proving Ground (APG)

Christina McClung  
Aberdeen Data Services Team (ADST)  
Logistics Engineering and Information Technology Company (Log.Sec)  
U.S. Army Aberdeen Proving Ground (APG)

### **Contributor:**

Bonnie Packer  
U.S. Army Environmental Center (AEC)  
U.S. Army Aberdeen Proving Ground (APG)

Matthew Banta  
Aberdeen Test and Support Services (ATSS)  
Sverdrup Technology, Inc.  
U.S. Army Aberdeen Proving Ground (APG)

## TABLE OF CONTENTS

|  | <u>PAGE</u> |
|--|-------------|
| 1.1 ACKNOWLEDGMENTS .....  | i           |
| <br><b><u>SECTION 1. GENERAL INFORMATION</u></b><br>                     |             |
| 1.1 BACKGROUND .....   | 1           |
| 1.2 SCORING OBJECTIVES .....   | 1           |
| 1.2.1 Scoring Methodology .....  | 1           |
| 1.2.2 Scoring Factors .....  | 2           |
| 1.3 STANDARD AND NONSTANDARD INERT ORDNANCE TARGETS .....                | 3           |
| <br><b><u>SECTION 2. DEMONSTRATION</u></b><br>                           |             |
| 2.1 DEMONSTRATOR INFORMATION .....                                       | 5           |
| 2.1.1 Demonstrator Point of Contact (POC) and Address .....              | 5           |
| 2.1.2 System Description .....   | 5           |
| 2.1.3 Data Processing Description .....                                  | 6           |
| 2.1.4 Data Submission Format .....                                       | 7           |
| 2.1.5 Demonstrator Quality Assurance (QA) and Quality Control (QC) ..... | 8           |
| 2.1.6 Additional Records .....   | 8           |
| 2.2 APG SITE INFORMATION .....   | 9           |
| 2.2.1 Location .....   | 9           |
| 2.2.2 Soil Type .....  | 9           |
| 2.2.3 Test Areas .....   | 9           |
| <br><b><u>SECTION 3. FIELD DATA</u></b><br>                              |             |
| 3.1 DATE OF FIELD ACTIVITIES .....                                       | 11          |
| 3.2 AREAS TESTED/NUMBER OF HOURS .....                                   | 11          |
| 3.3 TEST CONDITIONS .....  | 11          |
| 3.3.1 Weather Conditions .....   | 11          |
| 3.3.2 Field Conditions .....   | 11          |
| 3.3.3 Soil Moisture .....  | 11          |
| 3.4 FIELD ACTIVITIES .....   | 12          |
| 3.4.1 Setup/Mobilization .....   | 12          |
| 3.4.2 Calibration .....  | 12          |
| 3.4.3 Downtime Occasions .....   | 12          |
| 3.4.4 Data Collection .....  | 12          |
| 3.4.5 Demobilization .....   | 12          |
| 3.5 PROCESSING TIME .....  | 13          |
| 3.6 DEMONSTRATOR'S FIELD PERSONNEL .....                                 | 13          |
| 3.7 DEMONSTRATOR'S FIELD SURVEYING METHOD .....                          | 13          |
| 3.8 SUMMARY OF DAILY LOGS .....  | 13          |

**SECTION 4. TECHNICAL PERFORMANCE RESULTS**

|  | <b><u>PAGE</u></b> |
|--|--------------------|
| 4.1 ROC CURVES USING ALL ORDNANCE CATEGORIES .....             | 15                 |
| 4.2 ROC CURVES USING ORDNANCE LARGER THAN 20 MM .....          | 16                 |
| 4.3 PERFORMANCE SUMMARIES .....                                | 18                 |
| 4.4 EFFICIENCY, REJECTION RATES, AND TYPE CLASSIFICATION ..... | 19                 |
| 4.5 LOCATION ACCURACY .....                                    | 19                 |

**SECTION 5. ON-SITE LABOR COSTS**

**SECTION 6. COMPARISON OF RESULTS TO BLIND GRID DEMONSTRATION**

**SECTION 7. APPENDIXES**

|                               |     |
|-------------------------------|-----|
| A TERMS AND DEFINITIONS ..... | A-1 |
| B DAILY WEATHER LOGS .....    | B-1 |
| C SOIL MOISTURE .....         | C-1 |
| D DAILY ACTIVITY LOGS .....   | D-1 |
| E REFERENCES .....            | E-1 |
| F ABBREVIATIONS .....         | F-1 |

## **SECTION 1. GENERAL INFORMATION**

### **1.1 BACKGROUND**

Technologies under development for the detection and discrimination of munitions and explosives of concern (MEC) – i.e. unexploded ordnance (UXO) and discarded military munitions (DMM) require testing so that their performance can be characterized. To that end, Standardized Test Sites have been developed at Aberdeen Proving Ground (APG), Maryland and U.S. Army Yuma Proving Ground (YPG), Arizona. These test sites provide a diversity of geology, climate, terrain, and weather as well as diversity in ordnance and clutter. Testing at these sites is independently administered and analyzed by the government for the purposes of characterizing technologies, tracking performance with system development, comparing performance of different systems, and comparing performance in different environments.

The Standardized UXO Technology Demonstration Site Program is a multi-agency program spearheaded by the U.S. Army Environmental Center (AEC). The U.S. Army Aberdeen Test Center (ATC) and the U.S. Army Corps of Engineers Engineering Research and Development Center (ERDC) provide programmatic support. The program is being funded and supported by the Environmental Security Technology Certification Program (ESTCP), the Strategic Environmental Research and Development Program (SERDP) and the Army Environmental Quality Technology Program (EQT).

### **1.2 SCORING OBJECTIVES**

The objective in the Standardized UXO Technology Demonstration Site Program is to evaluate the detection and discrimination capabilities of a given technology under various field and soil conditions. Inert munitions and clutter items are positioned in various orientations and depths in the ground.

The evaluation objectives are as follows:

- a. To determine detection and discrimination effectiveness under realistic scenarios that vary targets, geology, clutter, topography, and vegetation.
- b. To determine cost, time, and manpower requirements to operate the technology.
- c. To determine demonstrator's ability to analyze survey data in a timely manner and provide prioritized "Target Lists" with associated confidence levels.
- d. To provide independent site management to enable the collection of high quality, ground-truth, geo-referenced data for post-demonstration analysis.

#### **1.2.1 Scoring Methodology**

- a. The scoring of the demonstrator's performance is conducted in two stages. These two stages are termed the RESPONSE STAGE and DISCRIMINATION STAGE. For both stages, the probability of detection ( $P_d$ ) and the false alarms are reported as receiver-operating

characteristic (ROC) curves. False alarms are divided into those anomalies that correspond to emplaced clutter items, measuring the probability of false positive ( $P_{fp}$ ), and those that do not correspond to any known item, termed background alarms.

b. The RESPONSE STAGE scoring evaluates the ability of the system to detect emplaced targets without regard to ability to discriminate ordnance from other anomalies. For the blind grid RESPONSE STAGE, the demonstrator provides the scoring committee with a target response from each and every grid square along with a noise level below which target responses are deemed insufficient to warrant further investigation. This list is generated with minimal processing and, since a value is provided for every grid square, will include signals both above and below the system noise level.

c. The DISCRIMINATION STAGE evaluates the demonstrator's ability to correctly identify ordnance as such and to reject clutter. For the blind grid DISCRIMINATION STAGE, the demonstrator provides the scoring committee with the output of the algorithms applied in the discrimination-stage processing for each grid square. The values in this list are prioritized based on the demonstrator's determination that a grid square is likely to contain ordnance. Thus, higher output values are indicative of higher confidence that an ordnance item is present at the specified location. For digital signal processing, priority ranking is based on algorithm output. For other discrimination approaches, priority ranking is based on human (subjective) judgment. The demonstrator also specifies the threshold in the prioritized ranking that provides optimum performance, (i.e. that is expected to retain all detected ordnance and rejects the maximum amount of clutter).

d. The demonstrator is also scored on EFFICIENCY and REJECTION RATIO, which measures the effectiveness of the discrimination stage processing. The goal of discrimination is to retain the greatest number of ordnance detections from the anomaly list, while rejecting the maximum number of anomalies arising from non-ordnance items. EFFICIENCY measures the fraction of detected ordnance retained after discrimination, while the REJECTION RATIO measures the fraction of false alarms rejected. Both measures are defined relative to performance at the demonstrator-supplied level below which all responses are considered noise, i.e., the maximum ordnance detectable by the sensor and its accompanying false positive rate or background alarm rate.

e. All scoring factors are generated utilizing the Standardized UXO Probability and Plot Program, version 3.1.1.

### **1.2.2 Scoring Factors**

Factors to be measured and evaluated as part of this demonstration include:

a. Response Stage ROC curves:

(1) Probability of Detection ( $P_d^{res}$ ).

(2) Probability of False Positive ( $P_{fp}^{res}$ ).

(3) Background Alarm Rate ( $BAR^{res}$ ) or Probability of Background Alarm ( $P_{BA}^{res}$ ).

b. Discrimination Stage ROC curves:

- (1) Probability of Detection ( $P_d^{\text{disc}}$ ).
- (2) Probability of False Positive ( $P_{\text{fp}}^{\text{disc}}$ ).
- (3) Background Alarm Rate ( $\text{BAR}^{\text{disc}}$ ) or Probability of Background Alarm ( $P_{\text{BA}}^{\text{disc}}$ ).

c. Metrics:

- (1) Efficiency (E).
- (2) False Positive Rejection Rate ( $R_{\text{fp}}$ ).
- (3) Background Alarm Rejection Rate ( $R_{\text{BA}}$ ).

d. Other:

- (1) Probability of Detection by Size and Depth.
- (2) Classification by type (i.e., 20-mm, 40-mm, 105-mm, etc.).
- (3) Location accuracy.
- (4) Equipment setup, calibration time and corresponding man-hour requirements.
- (5) Survey time and corresponding man-hour requirements.
- (6) Reacquisition/resurvey time and man-hour requirements (if any).
- (7) Downtime due to system malfunctions and maintenance requirements.

### **1.3 STANDARD AND NONSTANDARD INERT ORDNANCE TARGETS**

The standard and nonstandard ordnance items emplaced in the test areas are listed in Table 1. Standardized targets are members of a set of specific ordnance items that have identical properties to all other items in the set (caliber, configuration, size, weight, aspect ratio, material, filler, magnetic remanence, and nomenclature). Nonstandard targets are ordnance items having properties that differ from those in the set of standardized targets.

**TABLE 1. INERT ORDNANCE TARGETS**

| <b>Standard Type</b>         | <b>Nonstandard (NS)</b> |
|------------------------------|-------------------------|
| 20-mm Projectile M55         | 20-mm Projectile M55    |
|                              | 20-mm Projectile M97    |
| 40-mm Grenades M385          | 40-mm Grenades M385     |
| 40-mm Projectile MKII Bodies | 40-mm Projectile M813   |
| BDU-28 Submunition           |                         |
| BLU-26 Submunition           |                         |
| M42 Submunition              |                         |
| 57-mm Projectile APC M86     |                         |
| 60-mm Mortar M49A3           | 60-mm Mortar (JPG)      |
|                              | 60-mm Mortar M49        |
| 2.75-inch Rocket M230        | 2.75-inch Rocket M230   |
|                              | 2.75-inch Rocket XM229  |
| MK 118 ROCKEYE               |                         |
| 81-mm Mortar M374            | 81-mm Mortar (JPG)      |
|                              | 81-mm Mortar M374       |
| 105-mm HEAT Rounds M456      |                         |
| 105-mm Projectile M60        | 105-mm Projectile M60   |
| 155-mm Projectile M483A1     | 155-mm Projectile M483A |
|                              | 500-lb Bomb             |
|                              | M75 Submunition         |

JPG = Jefferson Proving Ground

HEAT = high-explosive antitank

## **SECTION 2. DEMONSTRATION**

### **2.1 DEMONSTRATOR INFORMATION**

#### **2.1.1 Demonstrator Point of Contact (POC) and Address**

Address: VF Warner and Associates, Inc.  
6832 Old Dominion Drive  
McLean, VA 22101

#### **2.1.2 System Description (provided by demonstrator)**

The core component of the AMOS metal detector (fig. 1) is a linear multi-channel sensor array consisting of a two-meter-wide transmitter coil and 16 receiver coils, mounted on a robust, all-terrain trailer.




Figure 1. Demonstrator's system, vehicle based Multi Channel Detector System (AMOS).

The AMOS detector unit consists of the following main components:

- Lower sensor level (dimensions: 2.16 x 1.00 meter).
- Upper sensor level (dimensions: 2.03 x 0.45 meter).
- Reference coil level (dimensions: 0.51 x 0.49 meter).

A special wheel suspension system ensures that the measurement system operates parallel to the terrain surface at a constant distance from the ground. This design makes sure that reproducible signatures are generated. It also enables the data from the individual lanes to be combined into a complete map without the appearance of virtual objects.

The physical measurement principle is based on the verification of an induced eddy current in a metallic body. With AMOS, active stimulation occurs by impulses via a transmitter coil with an eddy current that is switched off in a time interval of several microseconds. Temporal alteration of the primary magnetic field generated by the transmitter coil induces an eddy current in a metallic body located within the primary field. Owing to the finite conductivity, the eddy current induced in the interior and exterior of the body diminishes exponentially as time elapses.

Scanning performance in hectares per hour ( $P = v \times b$ ): 0.7 ha/ h

- with a scanning width (b) of: 1.8 meter
- at a scanning velocity (v) of: 1.1 m / s

Attainable accuracy of location (x,y)

- with an object depth of < 0.4meter                      0.25 meter (circular error)
- with an object depth of 0.4 – 1.5meter                0.50 meter (circular error)
- Attainable accuracy of depth (z)                         $\pm 0.3$  meter

Detection performance for ferrous and nonferrous metals: will detect ammunition components 20-mm caliber and over at depths of up to 0.4 meter, and ammunition components 100-mm caliber and over at depths of up to 1 meter.

### **2.1.3 Data Processing Description (provided by demonstrator)**

The pre-processed sensor signals are recorded in a notebook computer and archived. These data are later used in producing an object location map and accompanying list of objects offline.

In order to enable an exact assignment of coordinates when mapping the location of objects, the current position of the sensor platform trailer is continuously calculated by means of a special differential Global Positioning System (GPS) (real time kinematic (RTK) GPS), and then recorded and linked with the corresponding measurement data and stored at the hard disk in a binary format.

During the scanning process, the following items appear in real time on the display of the operator's notebook computer:

- The position of the sensor platform.
- The actual route being traveled by the sensor platform trailer.

- The intended route of travel of the sensor platform trailer.
- The current measurement data.

These display items ensure complete coverage during scanning operations.

The incoming sensor signals and the accompanying RTK-GPS position coordinates are processed online. The 16-channel sensor electronics feature a resolution of 16 bits and a data repetition rate of 20 Hz per channel. The digitized measurement data and the RTK-GPS data are transmitted via an RS 232 interface.

The following software components are available for the acquisition, evaluation, and visualization of data:

- The MonMX data acquisition module.
- The DLMGPS GPS coordinates transformation module.
- MAGNETO® data evaluation and visualization module.

During measurement operations, the MonMX module carries out the time-synchronous recording of the GPS and sensor data on the notebook. The real-time depiction of sensor data and visualization of the RTK-GPS status make it possible to conduct a qualitative evaluation of the measurement data during the actual measurement process. Moreover, to assure effective scanning of large areas, the current position of the vehicle, its direction of travel, and the intended and actual path of the sensor platform are all depicted in real time. Following a measurement run, the recorded RTK-GPS information and sensor data are available on the notebook computer for further processing and analysis. The DLMGPS software is used for administering, transforming, and depicting the GPS data in various coordinate systems.

Various export functions enable the exchange of data with the system-inherent MAGNETO® evaluation and visualization module, as well as the conversion of data for use in other geophysical software systems.

With the aid of the MAGNETO® software module, the AMOS measurement data can be visualized and documented in various forms. This gives the user a rapid overview of the level of contamination in the area being scanned.

Furthermore, the module permits the interactive search for and localization of metallic objects within the scanned area. The position coordinates, depth and diameter of suspicious objects, are recorded on object lists and object maps.

#### **2.1.4 Data Submission Format**

Data were submitted for scoring in accordance with data submission protocols outlined in the Standardized UXO Technology Demonstration Site Handbook. These submitted data are not included in this report in order to protect ground truth information.

### **2.1.5 Demonstrator Quality Assurance (QA) and Quality Control (QC) (provided by demonstrator)**

QC. All information relating to one individual project is saved along with the measurement data itself. These data include the number of channels and their connection to information layers, the relative position of sensors with respect to the GPS-antenna, the compensation values for each channel, and the base naming convention for automatic data storage and file numbering. Sensors can be compensated for offsets automatically to reduce errors.

The sensor carrier is towed by a suitable vehicle or pushed/pulled by the operator itself. During active data acquisition a real-time navigation display shows the track along which the sensor array is being moved along with selected or all project tracks already surveyed. The navigation display can be switched from auto-scaling to following current position (moving-map display). Quality control with respect to the completeness of the surveyed area is ensured as any “white space” may be filled by navigating into the required areas to obtain maximum coverage. Where a survey baseline can be defined, parallel and suitably spaced survey lines can automatically be created.

QA. The MonMX software records 20 samples per second of sensor data. During data acquisition the system maintains synchronisation to the GPS-timing, and all raw data is stored and stamped with those time tags. Raw data is stored in multiple numbered files where numbering can be automatic or under operator control. During measurements, a status line constantly provides information about the quality of the GPS-positioning, the number of available satellites, and the synchronisation.

### **2.1.6 Additional Records**

The following record(s) by this vendor can be accessed via the Internet as MicroSoft Word documents at [www.uxotestsites.org](http://www.uxotestsites.org).

## 2.2 APG SITE INFORMATION

### 2.2.1 Location

The APG Standardized Test Site is located within a secured range area of the Aberdeen Area of APG. The Aberdeen Area of APG is located approximately 30 miles northeast of Baltimore at the northern end of the Chesapeake Bay. The Standardized Test Site encompasses 17 acres of upland and lowland flats, woods, and wetlands.

### 2.2.2 Soil Type

According to the soils survey conducted for the entire area of APG in 1998, the test site consists primarily of Elkton Series type soil (ref 2). The Elkton Series consists of very deep, slowly permeable, poorly drained soils. These soils formed in silty aeolin sediments and the underlying loamy alluvial and marine sediments. They are on upland and lowland flats and in depressions of the Mid-Atlantic Coastal Plain. Slopes range from 0 to 2 percent.

ERDC conducted a site-specific analysis in May of 2002 (ref 3). The results basically matched the soil survey mentioned above. Seventy percent of the samples taken were classified as silty loam. The majority (77 percent) of the soil samples had a measured water content between 15- and 30-percent with the water content decreasing slightly with depth.

For more details concerning the soil properties at the APG test site, go to [www.uxotestsites.org](http://www.uxotestsites.org) on the web to view the entire soils description report.

### 2.2.3 Test Areas

A description of the test site areas at APG is included in Table 2.

**TABLE 2. TEST SITE AREAS**

| <b>Area</b>      | <b>Description</b>  |
|------------------|---|
| Calibration Grid | Contains 14 standard ordnance items buried in six positions at various angles and depths to allow demonstrator equipment calibration. |
| Blind Grid       | Contains 400 grid cells in a 0.2-hectare (0.5 acre) site. The center of each grid cell contains ordnance, clutter or nothing.         |

## SECTION 3. FIELD DATA

### 3.1 DATE OF FIELD ACTIVITIES (23 through 25 January 2006)

### 3.2 AREAS TESTED/NUMBER OF HOURS

Areas tested and total number of hours operated at each site are summarized in Table 3.

**TABLE 3. AREAS TESTED AND  
NUMBER OF HOURS**

| Area              | Number of Hours |
|-------------------|-----------------|
| Calibration Lanes | 1.33            |
| Blind Grid        | 1.33            |

### 3.3 TEST CONDITIONS

#### 3.3.1 Weather Conditions

An APG weather station located approximately one mile west of the test site was used to record average temperature and precipitation on a half hour basis for each day of operation. The temperatures listed in Table 4 represent the average temperature during field operations from 0700 to 1700 hours while precipitation data represents a daily total amount of rainfall. Hourly weather logs used to generate this summary are provided in Appendix B.

**TABLE 4. TEMPERATURE/PRECIPITATION DATA SUMMARY**

| Date, 2006 | Average Temperature, °F | Total Daily Precipitation, in. |
|------------|-------------------------|--------------------------------|
| 23 January | 40.7                    | 0.89                           |
| 24 January | 40.7                    | 0.08                           |
| 25 January | 39.4                    | 0.02                           |

#### 3.3.2 Field Conditions

VF Warner tested the AMOS from 23 through 25 January in rainy muddy conditions.

#### 3.3.3 Soil Moisture

Three soil probes were placed at various locations within the site to capture soil moisture data: calibration, mogul, open field, and wooded areas. Measurements were collected in percent moisture and were taken twice daily (morning and afternoon) from five different soil depths (1 to 6 in., 6 to 12 in., 12 to 24 in., 24 to 36 in., and 36 to 48 in.) from each probe. Soil moisture logs are included in Appendix C.

### **3.4 FIELD ACTIVITIES**

#### **3.4.1 Setup/Mobilization**

These activities included initial mobilization and daily equipment preparation and break down. A two-person crew took 3 hours and 45 minutes to perform the initial setup and mobilization. There was no time spent for daily equipment preparation or for end of the day equipment break down.

#### **3.4.2 Calibration**

VF Warner spent a total of 1-hour and 20 minutes in the calibration lanes with 40 minutes spent collecting data.

#### **3.4.3 Downtime Occasions**

Occasions of downtime are grouped into five categories: equipment/data checks or equipment maintenance, equipment failure and repair, weather, Demonstration Site issues, or breaks/lunch. All downtime is included for the purposes of calculating labor costs (section 5) except for downtime due to Demonstration Site issues. Demonstration Site issues, while noted in the Daily Log, are considered non-chargeable downtime for the purposes of calculating labor costs and are not discussed. Breaks and lunches are discussed in this section and billed to the total Site Survey area.

**3.4.3.1 Equipment/data checks, maintenance.** Equipment data checks and maintenance activities accounted for none of the site usage time. These activities included changing out batteries and routine data checks to ensure the data was being properly recorded/collected. VF Warner spent an additional 45 minutes for breaks and lunches.

**3.4.3.2 Equipment failure or repair.** No time was needed to resolve equipment failures that occurred while surveying the blind grid.

**3.4.3.3 Weather.** No weather delays occurred during the survey.

#### **3.4.4 Data Collection**

VF Warner spent a total time of 1-hour and 20 minutes in the blind grid area with 40 minutes spent collecting data.

#### **3.4.5 Demobilization**

The VF Warner survey crew went on to conduct a full demonstration of the site. Therefore, demobilization did not occur until 25 January 2005. On that day, it took the crew 4 hours and 15 minutes to break down and pack up their equipment.

### **3.5 PROCESSING TIME**

VF Warner submitted the raw data from the demonstration activities on the last day of the demonstration, as required. The scoring submittal data was also provided within the required 30-day timeframe.

### **3.6 DEMONSTRATOR'S FIELD PERSONNEL**

Dr. Christian Bittorf  
Dr. Andreas Fischer

### **3.7 DEMONSTRATOR'S FIELD SURVEYING METHOD**

The VF Warner team surveyed the site using a GPS system in a linear pattern.

### **3.8 SUMMARY OF DAILY LOGS**

Daily logs capture all field activities during this demonstration and are located in Appendix D. Activities pertinent to this specific demonstration are indicated in highlighted text.

## SECTION 4. TECHNICAL PERFORMANCE RESULTS

### 4.1 ROC CURVES USING ALL ORDNANCE CATEGORIES

Figure 2 shows the probability of detection for the response stage ( $P_d^{\text{res}}$ ) and the discrimination stage ( $P_d^{\text{disc}}$ ) versus their respective probability of false positive. Figure 3 shows both probabilities plotted against their respective probability of background alarm. Both figures use horizontal lines to illustrate the performance of the demonstrator at two demonstrator-specified points: at the system noise level for the response stage, representing the point below which targets are not considered detectable, and at the demonstrator's recommended threshold level for the discrimination stage, defining the subset of targets the demonstrator would recommend digging based on discrimination. Note that all points have been rounded to protect the ground truth.




Figure 2. AMOS/towed blind grid probability of detection for response and discrimination stages versus their respective probability of false positive over all ordnance categories combined.




Figure 3. AMOS/towed blind grid probability of detection for response and discrimination stages versus their respective probability of background alarm over all ordnance categories combined.

#### 4.2 ROC CURVES USING ORDNANCE LARGER THAN 20 MM

Figure 4 shows the probability of detection for the response stage ( $P_d^{\text{res}}$ ) and the discrimination stage ( $P_d^{\text{disc}}$ ) versus their respective probability of false positive when only targets larger than 20 mm are scored. Figure 5 shows both probabilities plotted against their respective probability of background alarm. Both figures use horizontal lines to illustrate the performance of the demonstrator at two demonstrator-specified points: at the system noise level for the response stage, representing the point below which targets are not considered detectable, and at the demonstrator's recommended threshold level for the discrimination stage, defining the subset of targets the demonstrator would recommend digging based on discrimination. Note that all points have been rounded to protect the ground truth.




Figure 4. AMOS/towed blind grid probability of detection for response and discrimination stages versus their respective probability of false positive for all ordnance larger than 20 mm.




Figure 5. AMOS/towed blind grid probability of detection for response and discrimination stages versus their respective probabilities of background alarm for all ordnance larger than 20 mm.

### 4.3 PERFORMANCE SUMMARIES

Results for the blind grid test broken out by size, depth and nonstandard ordnance are presented in Table 5 (for cost results, see section 5). Results by size and depth include both standard and nonstandard ordnance. The results by size show how well the demonstrator did at detecting/discriminating ordnance of a certain caliber range (see app A for size definitions). The results are relative to the number of ordnance items emplaced. Depth is measured from the geometric center of anomalies.

The RESPONSE STAGE results are derived from the list of anomalies above the demonstrator-provided noise level. The results for the DISCRIMINATION STAGE are derived from the demonstrator's recommended threshold for optimizing UXO field cleanup by minimizing false digs and maximizing ordnance recovery. The lower 90 percent confidence limit on probability of detection and  $P_{fp}$  was calculated assuming that the number of detections and false positives are binomially distributed random variables. All results in Table 5 have been rounded to protect the ground truth. However, lower confidence limits were calculated using actual results.

**TABLE 5. SUMMARY OF BLIND GRID RESULTS FOR THE AMOS/TOWED**

| Metric                      | Overall | Standard | Nonstandard | By Size |        |       | By Depth, m |           |      |
|-----------------------------|---------|----------|-------------|---------|--------|-------|-------------|-----------|------|
|                             |         |          |             | Small   | Medium | Large | < 0.3       | 0.3 to <1 | >= 1 |
| <b>RESPONSE STAGE</b>       |         |          |             |         |        |       |             |           |      |
| $P_d$                       | 0.65    | 0.70     | 0.55        | 0.70    | 0.50   | 0.80  | 0.85        | 0.60      | 0.30 |
| $P_d$ Low 90% Conf          | 0.57    | 0.59     | 0.45        | 0.59    | 0.39   | 0.55  | 0.72        | 0.48      | 0.16 |
| $P_d$ Upper 90% Conf        | 0.71    | 0.77     | 0.69        | 0.79    | 0.64   | 0.95  | 0.91        | 0.71      | 0.50 |
| $P_{fp}$                    | 0.80    | -        | -           | -       | -      | -     | 0.85        | 0.80      | 0.50 |
| $P_{fp}$ Low 90% Conf       | 0.73    | -        | -           | -       | -      | -     | 0.76        | 0.69      | 0.20 |
| $P_d$ Upper 90% Conf        | 0.85    | -        | -           | -       | -      | -     | 0.92        | 0.86      | 0.80 |
| $P_{ba}$                    | 0.25    | -        | -           | -       | -      | -     | -           | -         | -    |
| <b>DISCRIMINATION STAGE</b> |         |          |             |         |        |       |             |           |      |
| $P_d$                       | 0.65    | 0.70     | 0.55        | 0.70    | 0.50   | 0.80  | 0.85        | 0.60      | 0.30 |
| $P_d$ Low 90% Conf          | 0.57    | 0.59     | 0.45        | 0.59    | 0.39   | 0.55  | 0.72        | 0.48      | 0.16 |
| $P_d$ Upper 90% Conf        | 0.71    | 0.77     | 0.69        | 0.79    | 0.64   | 0.95  | 0.91        | 0.71      | 0.50 |
| $P_{fp}$                    | 0.80    | -        | -           | -       | -      | -     | 0.85        | 0.80      | 0.50 |
| $P_{fp}$ Low 90% Conf       | 0.73    | -        | -           | -       | -      | -     | 0.76        | 0.69      | 0.20 |
| $P_d$ Upper 90% Conf        | 0.85    | -        | -           | -       | -      | -     | 0.92        | 0.86      | 0.80 |
| $P_{ba}$                    | 0.25    | -        | -           | -       | -      | -     | -           | -         | -    |

Response Stage Noise Level: 1.50

Recommended Discrimination Stage Threshold: 0.50

Note: The recommended discrimination stage threshold values are provided by the demonstrator.

#### 4.4 EFFICIENCY, REJECTION RATES, AND TYPE CLASSIFICATION

Efficiency and rejection rates are calculated to quantify the discrimination ability at specific points of interest on the ROC curve: (1) at the point where no decrease in  $P_d$  is suffered (i.e., the efficiency is by definition equal to one) and (2) at the operator selected threshold. These values are reported in Table 6.

**TABLE 6. EFFICIENCY AND REJECTION RATES**

|                       | <b>Efficiency (E)</b> | <b>False Positive Rejection Rate</b> | <b>Background Alarm Rejection Rate</b> |
|-----------------------|-----------------------|--------------------------------------|--|
| At Operating Point    | 1.00                  | 0.00                                 | 0.00                                   |
| With No Loss of $P_d$ | 1.00                  | 0.00                                 | 0.00                                   |

At the demonstrator's recommended setting, the ordnance items that were detected and correctly discriminated were further scored on whether their correct type could be identified (table 7). Correct type examples include "20-mm projectile, 105-mm HEAT Projectile, and 2.75-inch Rocket". A list of the standard type declaration required for each ordnance item was provided to demonstrators prior to testing. For example, the standard type for the three example items are 20mmP, 105H, and 2.75in, respectively.

**TABLE 7. CORRECT TYPE CLASSIFICATION OF TARGETS CORRECTLY DISCRIMINATED AS UXO**

| <b>Size</b> | <b>Percentage Correct</b> |
|-------------|---------------------------|
| Small       | 0.00                      |
| Medium      | 0.00                      |
| Large       | 0.00                      |
| Overall     | 0.00                      |

Note: The demonstrator did not attempt to provide type classification.

#### 4.5 LOCATION ACCURACY

The mean location error and standard deviations appear in Table 8. These calculations are based on average missed depth for ordnance correctly identified in the discrimination stage. Depths are measured from the closest point of the ordnance to the surface. For the blind grid, only depth errors are calculated, since (X, Y) positions are known to be the centers of each grid square.

**TABLE 8. MEAN LOCATION ERROR AND  
STANDARD DEVIATION (M)**

|       | <b>Mean</b> | <b>Standard Deviation</b> |
|-------|-------------|---------------------------|
| Depth | 0.21        | 0.45                      |

## SECTION 5. ON-SITE LABOR COSTS

A standardized estimate for labor costs associated with this effort was calculated as follows: the first person at the test site was designated “supervisor”, the second person was designated “data analyst”, and the third and following personnel were considered “field support”. Standardized hourly labor rates were charged by title: supervisor at \$95.00/hour, data analyst at \$57.00/hour, and field support at \$28.50/hour.

Government representatives monitored on-site activity. All on-site activities were grouped into one of ten categories: initial setup/mobilization, daily setup/stop, calibration, collecting data, downtime due to break/lunch, downtime due to equipment failure, downtime due to equipment/data checks or maintenance, downtime due to weather, downtime due to demonstration site issue, or demobilization. See Appendix D for the daily activity log. See section 3.4 for a summary of field activities.

The standardized cost estimate associated with the labor needed to perform the field activities is presented in Table 9. Note that calibration time includes time spent in the Calibration Lanes as well as field calibrations. “Site survey time” includes daily setup/stop time, collecting data, breaks/lunch, downtime due to equipment/data checks or maintenance, downtime due to failure, and downtime due to weather.

**TABLE 9. ON-SITE LABOR COSTS**

|                      | <b>No. People</b> | <b>Hourly Wage</b> | <b>Hours</b> | <b>Cost</b>     |
|----------------------|-------------------|--------------------|--------------|-----------------|
| <b>Initial Setup</b> |                   |                    |              |                 |
| Supervisor           | 1                 | \$95.00            | 3.75         | \$356.25        |
| Data Analyst         | 1                 | 57.00              | 3.75         | 213.75          |
| Field Support        | 0                 | 28.50              | 0.00         | 0.00            |
| SubTotal             |                   |                    |              | <b>\$570.00</b> |
| <b>Calibration</b>   |                   |                    |              |                 |
| Supervisor           | 1                 | \$95.00            | 0.96         | \$126.35        |
| Data Analyst         | 1                 | 57.00              | 0.96         | 75.81           |
| Field Support        | 0                 | 28.50              | 0.00         | 0.00            |
| SubTotal             |                   |                    |              | <b>\$202.16</b> |
| <b>Site Survey</b>   |                   |                    |              |                 |
| Supervisor           | 1                 | \$95.00            | 0.96         | \$126.35        |
| Data Analyst         | 1                 | 57.00              | 0.96         | 75.81           |
| Field Support        | 0                 | 28.50              | 0.00         | 0.00            |
| SubTotal             |                   |                    |              | <b>\$202.16</b> |

See notes at end of table.

**TABLE 9 (CONT'D)**

|                       | <b>No. People</b> | <b>Hourly Wage</b> | <b>Hours</b> | <b>Cost</b>       |
|-----------------------|-------------------|--------------------|--------------|-------------------|
| <b>Demobilization</b> |                   |                    |              |                   |
| Supervisor            | 1                 | \$95.00            | 4.25         | \$403.75          |
| Data Analyst          | 1                 | 57.00              | 4.25         | 242.25            |
| Field Support         | 0                 | 28.50              | 0.00         | 0.00              |
| Subtotal              |                   |                    |              | <b>\$646.00</b>   |
| Total                 |                   |                    |              | <b>\$1,620.32</b> |

Notes: Calibration time includes time spent in the calibration lanes as well as calibration before each data run.

Site Survey time includes daily setup/stop time, collecting data, breaks/lunch, downtime due to system maintenance, failure, and weather.

**SECTION 6. COMPARISON OF RESULTS TO DATE**

No comparisons to date.

## SECTION 7. APPENDIXES

### APPENDIX A. TERMS AND DEFINITIONS

#### GENERAL DEFINITIONS

Anomaly: Location of a system response deemed to warrant further investigation by the demonstrator for consideration as an emplaced ordnance item.

Detection: An anomaly location that is within  $R_{\text{halo}}$  of an emplaced ordnance item.

Munitions and Explosives Of Concern (MEC): Specific categories of military munitions that may pose unique explosive safety risks, including UXO as defined in 10 USC 101(e)(5), DMM as defined in 10 USC 2710(e)(2) and/or munitions constituents (e.g. TNT, RDX) as defined in 10 USC 2710(e)(3) that are present in high enough concentrations to pose an explosive hazard.

Emplaced Ordnance: An ordnance item buried by the government at a specified location in the test site.

Emplaced Clutter: A clutter item (i.e., non-ordnance item) buried by the government at a specified location in the test site.

$R_{\text{halo}}$ : A pre-determined radius about the periphery of an emplaced item (clutter or ordnance) within which a location identified by the demonstrator as being of interest is considered to be a response from that item. If multiple declarations lie within  $R_{\text{halo}}$  of any item (clutter or ordnance), the declaration with the highest signal output within the  $R_{\text{halo}}$  will be utilized. For the purpose of this program, a circular halo 0.5 meters in radius will be placed around the center of the object for all clutter and ordnance items less than 0.6 meters in length. When ordnance items are longer than 0.6 meters, the halo becomes an ellipse where the minor axis remains 1 meter and the major axis is equal to the length of the ordnance plus 1 meter.

Small Ordnance: Caliber of ordnance less than or equal to 40 mm (includes 20-mm projectile, 40-mm projectile, submunitions BLU-26, BLU-63, and M42).

Medium Ordnance: Caliber of ordnance greater than 40 mm and less than or equal to 81 mm (includes 57-mm projectile, 60-mm mortar, 2.75 in. Rocket, MK118 Rockeye, 81-mm mortar).

Large Ordnance: Caliber of ordnance greater than 81 mm (includes 105-mm HEAT, 105-mm projectile, 155-mm projectile, 500-pound bomb).

Shallow: Items buried less than 0.3 meter below ground surface.

Medium: Items buried greater than or equal to 0.3 meter and less than 1 meter below ground surface.

Deep: Items buried greater than or equal to 1 meter below ground surface.

Response Stage Noise Level: The level that represents the point below which anomalies are not considered detectable. Demonstrators are required to provide the recommended noise level for the Blind Grid test area.

Discrimination Stage Threshold: The demonstrator selected threshold level that they believe provides optimum performance of the system by retaining all detectable ordnance and rejecting the maximum amount of clutter. This level defines the subset of anomalies the demonstrator would recommend digging based on discrimination.

Binomially Distributed Random Variable: A random variable of the type which has only two possible outcomes, say success and failure, is repeated for  $n$  independent trials with the probability  $p$  of success and the probability  $1-p$  of failure being the same for each trial. The number of successes  $x$  observed in the  $n$  trials is an estimate of  $p$  and is considered to be a binomially distributed random variable.

## RESPONSE AND DISCRIMINATION STAGE DATA

The scoring of the demonstrator's performance is conducted in two stages. These two stages are termed the RESPONSE STAGE and DISCRIMINATION STAGE. For both stages, the probability of detection ( $P_d$ ) and the false alarms are reported as receiver operating characteristic (ROC) curves. False alarms are divided into those anomalies that correspond to emplaced clutter items, measuring the probability of false positive ( $P_{fp}$ ) and those that do not correspond to any known item, termed background alarms.

The RESPONSE STAGE scoring evaluates the ability of the system to detect emplaced targets without regard to ability to discriminate ordnance from other anomalies. For the RESPONSE STAGE, the demonstrator provides the scoring committee with the location and signal strength of all anomalies that the demonstrator has deemed sufficient to warrant further investigation and/or processing as potential emplaced ordnance items. This list is generated with minimal processing (e.g., this list will include all signals above the system noise threshold). As such, it represents the most inclusive list of anomalies.

The DISCRIMINATION STAGE evaluates the demonstrator's ability to correctly identify ordnance as such, and to reject clutter. For the same locations as in the RESPONSE STAGE anomaly list, the DISCRIMINATION STAGE list contains the output of the algorithms applied in the discrimination-stage processing. This list is prioritized based on the demonstrator's determination that an anomaly location is likely to contain ordnance. Thus, higher output values are indicative of higher confidence that an ordnance item is present at the specified location. For electronic signal processing, priority ranking is based on algorithm output. For other systems, priority ranking is based on human judgment. The demonstrator also selects the threshold that the demonstrator believes will provide "optimum" system performance, (i.e., that retains all the detected ordnance and rejects the maximum amount of clutter).

Note: The two lists provided by the demonstrator contain identical numbers of potential target locations. They differ only in the priority ranking of the declarations.

## RESPONSE STAGE DEFINITIONS

Response Stage Probability of Detection ( $P_d^{\text{res}}$ ):  $P_d^{\text{res}} = (\text{No. of response-stage detections})/(\text{No. of emplaced ordnance in the test site})$ .

Response Stage False Positive ( $fp^{\text{res}}$ ): An anomaly location that is within  $R_{\text{halo}}$  of an emplaced clutter item.

Response Stage Probability of False Positive ( $P_{fp}^{\text{res}}$ ):  $P_{fp}^{\text{res}} = (\text{No. of response-stage false positives})/(\text{No. of emplaced clutter items})$ .

Response Stage Background Alarm ( $ba^{\text{res}}$ ): An anomaly in a blind grid cell that contains neither emplaced ordnance nor an emplaced clutter item. An anomaly location in the open field or scenarios that is outside  $R_{\text{halo}}$  of any emplaced ordnance or emplaced clutter item.

Response Stage Probability of Background Alarm ( $P_{ba}^{\text{res}}$ ): Blind Grid only:  $P_{ba}^{\text{res}} = (\text{No. of response-stage background alarms})/(\text{No. of empty grid locations})$ .

Response Stage Background Alarm Rate ( $BAR^{\text{res}}$ ): Open Field only:  $BAR^{\text{res}} = (\text{No. of response-stage background alarms})/(\text{arbitrary constant})$ .

Note that the quantities  $P_d^{\text{res}}$ ,  $P_{fp}^{\text{res}}$ ,  $P_{ba}^{\text{res}}$ , and  $BAR^{\text{res}}$  are functions of  $t^{\text{res}}$ , the threshold applied to the response-stage signal strength. These quantities can therefore be written as  $P_d^{\text{res}}(t^{\text{res}})$ ,  $P_{fp}^{\text{res}}(t^{\text{res}})$ ,  $P_{ba}^{\text{res}}(t^{\text{res}})$ , and  $BAR^{\text{res}}(t^{\text{res}})$ .

## DISCRIMINATION STAGE DEFINITIONS

Discrimination: The application of a signal processing algorithm or human judgment to response-stage data that discriminates ordnance from clutter. Discrimination should identify anomalies that the demonstrator has high confidence correspond to ordnance, as well as those that the demonstrator has high confidence correspond to non-ordnance or background returns. The former should be ranked with highest priority and the latter with lowest.

Discrimination Stage Probability of Detection ( $P_d^{\text{disc}}$ ):  $P_d^{\text{disc}} = (\text{No. of discrimination-stage detections})/(\text{No. of emplaced ordnance in the test site})$ .

Discrimination Stage False Positive ( $fp^{\text{disc}}$ ): An anomaly location that is within  $R_{\text{halo}}$  of an emplaced clutter item.

Discrimination Stage Probability of False Positive ( $P_{fp}^{\text{disc}}$ ):  $P_{fp}^{\text{disc}} = (\text{No. of discrimination stage false positives})/(\text{No. of emplaced clutter items})$ .

Discrimination Stage Background Alarm ( $ba^{\text{disc}}$ ): An anomaly in a blind grid cell that contains neither emplaced ordnance nor an emplaced clutter item. An anomaly location in the open field or scenarios that is outside  $R_{\text{halo}}$  of any emplaced ordnance or emplaced clutter item.

Discrimination Stage Probability of Background Alarm ( $P_{ba}^{disc}$ ):  $P_{ba}^{disc} = (\text{No. of discrimination-stage background alarms})/(\text{No. of empty grid locations})$ .

Discrimination Stage Background Alarm Rate ( $BAR^{disc}$ ):  $BAR^{disc} = (\text{No. of discrimination-stage background alarms})/(\text{arbitrary constant})$ .

Note that the quantities  $P_d^{disc}$ ,  $P_{fp}^{disc}$ ,  $P_{ba}^{disc}$ , and  $BAR^{disc}$  are functions of  $t^{disc}$ , the threshold applied to the discrimination-stage signal strength. These quantities can therefore be written as  $P_d^{disc}(t^{disc})$ ,  $P_{fp}^{disc}(t^{disc})$ ,  $P_{ba}^{disc}(t^{disc})$ , and  $BAR^{disc}(t^{disc})$ .

## RECEIVER-OPERATING CHARACTERISTIC (ROC) CURVES

ROC curves at both the response and discrimination stages can be constructed based on the above definitions. The ROC curves plot the relationship between  $P_d$  versus  $P_{fp}$  and  $P_d$  versus  $BAR$  or  $P_{ba}$  as the threshold applied to the signal strength is varied from its minimum ( $t_{min}$ ) to its maximum ( $t_{max}$ ) value.<sup>1</sup> Figure A-1 shows how  $P_d$  versus  $P_{fp}$  and  $P_d$  versus  $BAR$  are combined into ROC curves. Note that the “res” and “disc” superscripts have been suppressed from all the variables for clarity.




Figure A-1. ROC curves for open field testing. Each curve applies to both the response and discrimination stages.

<sup>1</sup>Strictly speaking, ROC curves plot the  $P_d$  versus  $P_{ba}$  over a pre-determined and fixed number of detection opportunities (some of the opportunities are located over ordnance and others are located over clutter or blank spots). In an open field scenario, each system suppresses its signal strength reports until some bare-minimum signal response is received by the system. Consequently, the open field ROC curves do not have information from low signal-output locations, and, furthermore, different contractors report their signals over a different set of locations on the ground. These ROC curves are thus not true to the strict definition of ROC curves as defined in textbooks on detection theory. Note, however, that the ROC curves obtained in the Blind Grid test sites are true ROC curves.

## METRICS TO CHARACTERIZE THE DISCRIMINATION STAGE

The demonstrator is also scored on efficiency and rejection ratio, which measure the effectiveness of the discrimination stage processing. The goal of discrimination is to retain the greatest number of ordnance detections from the anomaly list, while rejecting the maximum number of anomalies arising from non-ordnance items. The efficiency measures the amount of detected ordnance retained by the discrimination, while the rejection ratio measures the fraction of false alarms rejected. Both measures are defined relative to the entire response list, i.e., the maximum ordnance detectable by the sensor and its accompanying false positive rate or background alarm rate.

Efficiency (E):  $E = P_d^{\text{disc}}(t^{\text{disc}})/P_d^{\text{res}}(t_{\text{min}}^{\text{res}})$ ; Measures (at a threshold of interest), the degree to which the maximum theoretical detection performance of the sensor system (as determined by the response stage  $t_{\text{min}}$ ) is preserved after application of discrimination techniques. Efficiency is a number between 0 and 1. An efficiency of 1 implies that all of the ordnance initially detected in the response stage was retained at the specified threshold in the discrimination stage,  $t^{\text{disc}}$ .

False Positive Rejection Rate ( $R_{\text{fp}}$ ):  $R_{\text{fp}} = 1 - [P_{\text{fp}}^{\text{disc}}(t^{\text{disc}})/P_{\text{fp}}^{\text{res}}(t_{\text{min}}^{\text{res}})]$ ; Measures (at a threshold of interest), the degree to which the sensor system's false positive performance is improved over the maximum false positive performance (as determined by the response stage  $t_{\text{min}}$ ). The rejection rate is a number between 0 and 1. A rejection rate of 1 implies that all emplaced clutter initially detected in the response stage were correctly rejected at the specified threshold in the discrimination stage.

Background Alarm Rejection Rate ( $R_{\text{ba}}$ ):

Blind Grid:  $R_{\text{ba}} = 1 - [P_{\text{ba}}^{\text{disc}}(t^{\text{disc}})/P_{\text{ba}}^{\text{res}}(t_{\text{min}}^{\text{res}})]$ .

Open Field:  $R_{\text{ba}} = 1 - [\text{BAR}^{\text{disc}}(t^{\text{disc}})/\text{BAR}^{\text{res}}(t_{\text{min}}^{\text{res}})]$ .

Measures the degree to which the discrimination stage correctly rejects background alarms initially detected in the response stage. The rejection rate is a number between 0 and 1. A rejection rate of 1 implies that all background alarms initially detected in the response stage were rejected at the specified threshold in the discrimination stage.

## CHI-SQUARE COMPARISON EXPLANATION:

The Chi-square test for differences in probabilities (or 2 x 2 contingency table) is used to analyze two samples drawn from two different populations to see if both populations have the same or different proportions of elements in a certain category. More specifically, two random samples are drawn, one from each population, to test the null hypothesis that the probability of event A (some specified event) is the same for both populations (ref 3).

A 2 x 2 contingency table is used in the Standardized UXO Technology Demonstration Site Program to determine if there is reason to believe that the proportion of ordnance correctly detected/discriminated by demonstrator X's system is significantly degraded by the more challenging terrain feature introduced. The test statistic of the 2 x 2 contingency table is the

Chi-square distribution with one degree of freedom. Since an association between the more challenging terrain feature and relatively degraded performance is sought, a one-sided test is performed. A significance level of 0.05 is chosen which sets a critical decision limit of 3.84 from the Chi-square distribution with one degree of freedom. It is a critical decision limit because if the test statistic calculated from the data exceeds this value, the two proportions tested will be considered significantly different. If the test statistic calculated from the data is less than this value, the two proportions tested will be considered not significantly different.

An exception must be applied when either a 0 or 100 percent success rate occurs in the sample data. The Chi-square test cannot be used in these instances. Instead, Fischer’s test is used and the critical decision limit for one-sided tests is the chosen significance level, which in this case is 0.05. With Fischer’s test, if the test statistic is less than the critical value, the proportions are considered to be significantly different.

Standardized UXO Technology Demonstration Site examples, where blind grid results are compared to those from the open field and open field results are compared to those from one of the scenarios, follow. It should be noted that a significant result does not prove a cause and effect relationship exists between the two populations of interest; however, it does serve as a tool to indicate that one data set has experienced a degradation in system performance at a large enough level than can be accounted for merely by chance or random variation. Note also that a result that is not significant indicates that there is not enough evidence to declare that anything more than chance or random variation within the same population is at work between the two data sets being compared.

Demonstrator X achieves the following overall results after surveying each of the three progressively more difficult areas using the same system (results indicate the number of ordnance detected divided by the number of ordnance emplaced):

|              | Blind Grid    | Open Field | Moguls      |
|--------------|---------------|------------|-------------|
| $P_d^{res}$  | 100/100 = 1.0 | 8/10 = .80 | 20/33 = .61 |
| $P_d^{disc}$ | 80/100 = 0.80 | 6/10 = .60 | 8/33 = .24  |

$P_d^{res}$ : BLIND GRID versus OPEN FIELD. Using the example data above to compare probabilities of detection in the response stage, all 100 ordnance out of 100 emplaced ordnance items were detected in the blind grid while 8 ordnance out of 10 emplaced were detected in the open field. Fischer’s test must be used since a 100 percent success rate occurs in the data. Fischer’s test uses the four input values to calculate a test statistic of 0.0075 that is compared against the critical value of 0.05. Since the test statistic is less than the critical value, the smaller response stage detection rate (0.80) is considered to be significantly less at the 0.05 level of significance. While a significant result does not prove a cause and effect relationship exists between the change in survey area and degradation in performance, it does indicate that the detection ability of demonstrator X’s system seems to have been degraded in the open field relative to results from the blind grid using the same system.

$P_d^{\text{disc}}$ : BLIND GRID versus OPEN FIELD. Using the example data above to compare probabilities of detection in the discrimination stage, 80 out of 100 emplaced ordnance items were correctly discriminated as ordnance in blind grid testing while 6 ordnance out of 10 emplaced were correctly discriminated as such in open field-testing. Those four values are used to calculate a test statistic of 1.12. Since the test statistic is less than the critical value of 3.84, the two discrimination stage detection rates are considered to be not significantly different at the 0.05 level of significance.

$P_d^{\text{res}}$ : OPEN FIELD versus MOGULS. Using the example data above to compare probabilities of detection in the response stage, 8 out of 10 and 20 out of 33 are used to calculate a test statistic of 0.56. Since the test statistic is less than the critical value of 3.84, the two response stage detection rates are considered to be not significantly different at the 0.05 level of significance.

$P_d^{\text{disc}}$ : OPEN FIELD versus MOGULS. Using the example data above to compare probabilities of detection in the discrimination stage, 6 out of 10 and 8 out of 33 are used to calculate a test statistic of 2.98. Since the test statistic is greater than the critical value of 3.84, the smaller discrimination stage detection rate is considered to be significantly less at the 0.05 level of significance. While a significant result does not prove a cause and effect relationship exists between the change in survey area and degradation in performance, it does indicate that the ability of demonstrator X to correctly discriminate seems to have been degraded by the mogul terrain relative to results from the flat open field using the same system.

## APPENDIX B. DAILY WEATHER LOGS

| <b>Date</b> | <b>Time, EST</b> | <b>Average Temperature, °F</b> | <b>Maximum Temperature, °F</b> | <b>Minimum Temperature, °F</b> | <b>Average Relative Humidity, %</b> | <b>Total Precipitation, in.</b> |
|-------------|------------------|--------------------------------|--------------------------------|--------------------------------|-------------------------------------|---------------------------------|
| 1/23/2006   | 01:00            | 34.7                           | 35.2                           | 34.3                           | 98                                  | 0.09                            |
| 1/23/2006   | 02:00            | 34.7                           | 35.1                           | 34.4                           | 99                                  | 0.07                            |
| 1/23/2006   | 03:00            | 35.5                           | 36.2                           | 34.6                           | 100                                 | 0.18                            |
| 1/23/2006   | 04:00            | 35.9                           | 36.4                           | 35.4                           | 100                                 | 0.18                            |
| 1/23/2006   | 05:00            | 36.8                           | 37.4                           | 36.1                           | 100                                 | 0.24                            |
| 1/23/2006   | 06:00            | 37.7                           | 38.2                           | 36.9                           | 100                                 | 0.08                            |
| 1/23/2006   | 07:00            | 38.5                           | 39.1                           | 37.9                           | 100                                 | 0.01                            |
| 1/23/2006   | 08:00            | 38.7                           | 39.1                           | 38.4                           | 100                                 | 0.01                            |
| 1/23/2006   | 09:00            | 38.9                           | 39.4                           | 38.4                           | 100                                 | 0.00                            |
| 1/23/2006   | 10:00            | 39.5                           | 40.0                           | 39.0                           | 100                                 | 0.00                            |
| 1/23/2006   | 11:00            | 39.9                           | 40.4                           | 39.4                           | 100                                 | 0.00                            |
| 1/23/2006   | 12:00            | 40.7                           | 41.6                           | 40.0                           | 100                                 | 0.00                            |
| 1/23/2006   | 13:00            | 41.6                           | 42.2                           | 41.0                           | 97                                  | 0.00                            |
| 1/23/2006   | 14:00            | 41.9                           | 42.4                           | 41.4                           | 96                                  | 0.03                            |
| 1/23/2006   | 15:00            | 42.5                           | 43.1                           | 42.0                           | 96                                  | 0.00                            |
| 1/23/2006   | 16:00            | 42.9                           | 43.3                           | 42.7                           | 95                                  | 0.00                            |
| 1/23/2006   | 17:00            | 42.9                           | 43.1                           | 42.5                           | 95                                  | 0.00                            |
| 1/23/2006   | 18:00            | 42.2                           | 42.9                           | 41.5                           | 95                                  | 0.00                            |
| 1/23/2006   | 19:00            | 41.6                           | 42.1                           | 41.2                           | 96                                  | 0.00                            |
| 1/23/2006   | 20:00            | 40.9                           | 41.6                           | 40.4                           | 97                                  | 0.00                            |
| 1/23/2006   | 21:00            | 40.7                           | 41.1                           | 40.3                           | 93                                  | 0.00                            |
| 1/23/2006   | 22:00            | 40.5                           | 41.0                           | 39.8                           | 93                                  | 0.00                            |
| 1/23/2006   | 23:00            | 39.4                           | 40.3                           | 37.9                           | 95                                  | 0.00                            |
| 1/23/2006   | 23:59            | 36.5                           | 38.6                           | 34.2                           | 98                                  | 0.00                            |
| 1/24/2006   | 01:00            | 33.8                           | 36.1                           | 32.8                           | 100                                 | 0.00                            |
| 1/24/2006   | 02:00            | 32.6                           | 35.7                           | 31.1                           | 100                                 | 0.00                            |
| 1/24/2006   | 03:00            | 33.8                           | 34.7                           | 31.9                           | 100                                 | 0.00                            |
| 1/24/2006   | 04:00            | 33.7                           | 35.4                           | 30.9                           | 100                                 | 0.00                            |
| 1/24/2006   | 05:00            | 31.0                           | 32.1                           | 29.5                           | 100                                 | 0.00                            |
| 1/24/2006   | 06:00            | 30.2                           | 30.7                           | 29.5                           | 100                                 | 0.00                            |
| 1/24/2006   | 07:00            | 28.7                           | 30.0                           | 27.2                           | 100                                 | 0.00                            |
| 1/24/2006   | 08:00            | 27.4                           | 28.4                           | 26.4                           | 100                                 | 0.00                            |
| 1/24/2006   | 09:00            | 31.6                           | 35.3                           | 28.1                           | 100                                 | 0.00                            |
| 1/24/2006   | 10:00            | 37.2                           | 39.8                           | 34.9                           | 94                                  | 0.00                            |
| 1/24/2006   | 11:00            | 42.3                           | 44.4                           | 40.6                           | 78                                  | 0.00                            |
| 1/24/2006   | 12:00            | 45.9                           | 47.3                           | 44.1                           | 57                                  | 0.00                            |
| 1/24/2006   | 13:00            | 47.2                           | 48.0                           | 46.5                           | 53                                  | 0.00                            |
| 1/24/2006   | 14:00            | 46.8                           | 47.7                           | 46.2                           | 57                                  | 0.00                            |

| <b>Date</b> | <b>Time, EST</b> | <b>Average Temperature, °F</b> | <b>Maximum Temperature, °F</b> | <b>Minimum Temperature, °F</b> | <b>Average Relative Humidity, %</b> | <b>Total Precipitation, in.</b> |
|-------------|------------------|--------------------------------|--------------------------------|--------------------------------|-------------------------------------|---------------------------------|
| 1/24/2006   | 15:00            | 47.2                           | 47.7                           | 46.6                           | 60                                  | 0.00                            |
| 1/24/2006   | 16:00            | 47.2                           | 47.7                           | 46.7                           | 65                                  | 0.00                            |
| 1/24/2006   | 17:00            | 45.9                           | 47.2                           | 44.1                           | 67                                  | 0.00                            |
| 1/24/2006   | 18:00            | 41.7                           | 44.3                           | 39.7                           | 74                                  | 0.00                            |
| 1/24/2006   | 19:00            | 39.7                           | 40.9                           | 38.8                           | 74                                  | 0.00                            |
| 1/24/2006   | 20:00            | 39.8                           | 41.4                           | 38.0                           | 73                                  | 0.00                            |
| 1/24/2006   | 21:00            | 41.2                           | 41.8                           | 39.9                           | 69                                  | 0.00                            |
| 1/24/2006   | 22:00            | 39.2                           | 40.3                           | 37.2                           | 74                                  | 0.00                            |
| 1/24/2006   | 23:00            | 37.3                           | 41.5                           | 35.4                           | 92                                  | 0.08                            |
| 1/24/2006   | 23:59            | 35.2                           | 35.8                           | 34.3                           | 100                                 | 0.00                            |
| 1/25/2006   | 01:00            | 35.3                           | 36.1                           | 34.6                           | 100                                 | 0.00                            |
| 1/25/2006   | 02:00            | 34.4                           | 36.1                           | 32.3                           | 99                                  | 0.00                            |
| 1/25/2006   | 03:00            | 32.8                           | 34.2                           | 31.9                           | 100                                 | 0.00                            |
| 1/25/2006   | 04:00            | 31.4                           | 33.3                           | 29.7                           | 100                                 | 0.00                            |
| 1/25/2006   | 05:00            | 31.0                           | 32.9                           | 29.4                           | 100                                 | 0.00                            |
| 1/25/2006   | 06:00            | 34.3                           | 36.1                           | 30.7                           | 88                                  | 0.00                            |
| 1/25/2006   | 07:00            | 36.0                           | 37.2                           | 34.9                           | 80                                  | 0.00                            |
| 1/25/2006   | 08:00            | 35.9                           | 37.2                           | 34.8                           | 79                                  | 0.00                            |
| 1/25/2006   | 09:00            | 37.3                           | 38.5                           | 35.6                           | 79                                  | 0.01                            |
| 1/25/2006   | 10:00            | 37.6                           | 40.4                           | 35.5                           | 76                                  | 0.00                            |
| 1/25/2006   | 11:00            | 40.6                           | 41.7                           | 39.9                           | 57                                  | 0.00                            |
| 1/25/2006   | 12:00            | 41.0                           | 42.2                           | 40.3                           | 53                                  | 0.01                            |
| 1/25/2006   | 13:00            | 40.3                           | 41.2                           | 39.8                           | 51                                  | 0.00                            |
| 1/25/2006   | 14:00            | 41.1                           | 41.8                           | 40.6                           | 48                                  | 0.00                            |
| 1/25/2006   | 15:00            | 41.5                           | 42.3                           | 40.7                           | 49                                  | 0.00                            |
| 1/25/2006   | 16:00            | 41.4                           | 42.2                           | 40.7                           | 48                                  | 0.00                            |
| 1/25/2006   | 17:00            | 40.7                           | 41.3                           | 40.0                           | 47                                  | 0.00                            |
| 1/25/2006   | 18:00            | 38.9                           | 40.4                           | 37.6                           | 50                                  | 0.00                            |
| 1/25/2006   | 19:00            | 37.4                           | 38.0                           | 36.7                           | 49                                  | 0.00                            |
| 1/25/2006   | 20:00            | 36.3                           | 37.2                           | 35.6                           | 50                                  | 0.00                            |
| 1/25/2006   | 21:00            | 35.5                           | 36.2                           | 34.9                           | 52                                  | 0.00                            |
| 1/25/2006   | 22:00            | 34.9                           | 35.5                           | 34.3                           | 49                                  | 0.00                            |
| 1/25/2006   | 23:00            | 34.3                           | 34.9                           | 33.6                           | 47                                  | 0.00                            |
| 1/25/2006   | 23:59            | 33.7                           | 34.2                           | 33.3                           | 49                                  | 0.00                            |

## APPENDIX C. SOIL MOISTURE

**Date:** 1/23/2006

**Times:** 1100 hours through 1600 hours

| Probe Location    | Layer, in. | AM Reading, % | PM Reading, % |
|-------------------|------------|---------------|---------------|
| Wet Area          | 0 to 6     | NA            | NA            |
|                   | 6 to 12    | NA            | NA            |
|                   | 12 to 24   | NA            | NA            |
|                   | 24 to 36   | NA            | NA            |
|                   | 36 to 48   | NA            | NA            |
| Wooded Area       | 0 to 6     | NA            | NA            |
|                   | 6 to 12    | NA            | NA            |
|                   | 12 to 24   | NA            | NA            |
|                   | 24 to 36   | NA            | NA            |
|                   | 36 to 48   | NA            | NA            |
| Open Area         | 0 to 6     | NA            | NA            |
|                   | 6 to 12    | NA            | NA            |
|                   | 12 to 24   | NA            | NA            |
|                   | 24 to 36   | NA            | NA            |
|                   | 36 to 48   | NA            | NA            |
| Calibration Lanes | 0 to 6     | 2.8           | 3.0           |
|                   | 6 to 12    | 15.9          | 15.7          |
|                   | 12 to 24   | 24.7          | 24.9          |
|                   | 24 to 36   | 28.9          | 28.8          |
| Blind Grid/Moguls | 0 to 6     | 3.6           | 3.5           |
|                   | 6 to 12    | 5.8           | 5.9           |
|                   | 12 to 24   | 24.8          | 24.8          |
|                   | 24 to 36   | 4.9           | 5.2           |
|                   | 36 to 48   | 4.5           | 4.6           |

| Date      | No. of People | Area-Tested       | Status Start Time | Status Stop Time | Duration, min. | Op Stat Code | Operational Status | Operational Status - Comments  | Track Method | Track Method= Other Explain | Pattern | Field Conditions |
|-----------|---------------|-------------------|-------------------|------------------|----------------|--------------|--------------------|--|--------------|-----------------------------|---------|------------------|
| 1/23/2006 | 3             | CALIBRATION LANES | 1000              | 1345             | 225            | 1            | INITIAL SET-UP     | -  | GPS          | NA                          | LINEAR  | RAIN MUDDY       |
| 1/23/2006 | 3             | CALIBRATION LANES | 1345              | 1430             | 45             | 5            | BREAK/LUNCH        | -  | GPS          | NA                          | LINEAR  | RAIN MUDDY       |
| 1/23/2006 | 3             | CALIBRATION LANES | 1430              | 1550             | 80             | 4            | COLLECTING DATA    | HALF TIME WAS SPENT IN CALIBRATION LANE AND OTHER HALF IN BLIND GRID | GPS          | NA                          | LINEAR  | RAIN MUDDY       |
| 1/23/2006 | 3             | CALIBRATION LANES | 1550              | 1625             | 35             | 3            | DAILY START, STOP  | HALF TIME WAS SPENT IN CALIBRATION LANE AND OTHER HALF IN BLIND GRID | GPS          | NA                          | LINEAR  | RAIN MUDDY       |
| 1/25/2006 | 3             | CALIBRATION LANES | 1115              | 1530             | 255            | 10           | DEMOBILIZATION     | -  | GPS          | NA                          | LINEAR  | RAIN MUDDY       |

Note: Activities pertinent to this specific demonstration are indicated in highlighted text.

## **APPENDIX E. REFERENCES**

1. Standardized UXO Technology Demonstration Site Handbook, DTC Project No. 8-CO-160-000-473, Report No. ATC-8349, March 2002.
2. Aberdeen Proving Ground Soil Survey Report, October 1998.
3. Data Summary, UXO Standardized Test Site: APG Soils Description, May 2002.
4. Yuma Proving Ground Soil Survey Report, May 2003.

## APPENDIX F. ABBREVIATIONS

|         |   |  |
|---------|---|--|
| ADST    | = | Aberdeen Data Services Team  |
| AEC     | = | U.S. Army Environmental Center   |
| APG     | = | Aberdeen Proving Ground  |
| ATC     | = | U.S. Army Aberdeen Test Center   |
| ATSS    | = | Aberdeen Test and Support Services                                       |
| DDM     | = | discarded military munitions   |
| ERDC    | = | U.S. Army Corps of Engineers Engineering Research and Development Center |
| ESTCP   | = | Environmental Security Technology Certification Program                  |
| EQT     | = | Army Environmental Quality Technology Program                            |
| GPS     | = | Global Positioning System  |
| HEAT    | = | high explosive antitank  |
| JPG     | = | Jefferson Proving Ground   |
| Log.Sec | = | Logistics Engineering and Information Technology Company                 |
| MEC     | = | munitions and explosives of concern                                      |
| NS      | = | nonstandard  |
| POC     | = | point of contact   |
| QA      | = | quality assurance  |
| QC      | = | quality control  |
| RH      | = | relative humidity  |
| ROC     | = | receiver-operating characteristic  |
| RTK     | = | real time kinematic  |
| SERDP   | = | Strategic Environmental Research and Development Program                 |
| UXO     | = | unexploded ordnance  |
| YPG     | = | U.S. Army Yuma Proving Ground  |

Secondary distribution is controlled by Commander, U.S. Army Environmental Center,  
ATTN: SFIM-AEC-ATT.